

DECLARATION OF PERFORMANCE Nº 2013071201

1. Product-type:
High Pressure compact laminate reference FACADE S (Thickness: 6 - 22 mm)
2. Name & contact address of the manufacturer:
Parklex International,s.l.
Polígono Alkaiga, C/Baldrun 1
31.780 Bera – Navarra (Spain)
3. Intended use of the construction product:
As external finishes in walls or ceilings, subject to reaction to fire regulations
4. System of assessment and verification of the constancy of performance: 3
5. Notified body:
 - Tecnia Research & Innovation NB 1292
 - Reaction to fire for initial type testing
 - System 3

6. Declared performance:

Essential characteristics	Performance	Harmonized technical specifications
Reaction to fire	C-s1;d0	EN 438-7:2005
Resistance to fire	NPD	
Water vapour permeability	Wet cup Dry cup	
Resistance to fixings	6mm thickness 8 mm thickness ≥ 10 mm thickness	
Direct airborne sound insulation	NPD	
Bonding Strength	NPD ¹	
Flexural tensile strength	PASS	
Thermal conductivity	≤ 0,3 w / m * k	
Content of pentachlorophenol	NPD ¹	
Release of formaldehyde	NPD ²	
Sound absorption	NPD ²	
Thermal shock resistance	PASS	
Durability: Resistance to wet conditions	PASS	
Durability: Density	PASS	

¹ Applicable only to HPL composite panels

² Applicable only to panels intended for internal use

- The performance of the product identified in point 1 is in conformity with the declared performance in point 6
- This declaration performance is issued under the sole responsibility of the manufacturer identified in point 2
- Signed for and on behalf of the manufacturer by: Iñigo Rodrigo (General Manager)

Signature:

Place and date of issue:


Parklex®
www.parklex.com

Bera, the 31st of May 2017