

## DECLARATION OF PERFORMANCE Nº 2014050805

1. Product-type:  
High Pressure compact laminate reference WET INTERNAL F (Thickness: 6 - 22 mm)
2. Name & contact address of the manufacturer:  
Parklex International,s.l.  
Polígono Alkaiga, C/Baldrun 1  
31.780 Bera – Navarra (Spain)
3. Intended use of the construction product:  
As internal finishes in walls or ceilings, subject to reaction to fire regulations
4. System of assessment and verification of the constancy of performance: 1
5. Notified body:
  - Tecnalía R&I Certificación NB 1239
  - Evaluation of the Factory Production Control
  - Reaction to fire for initial type testing
  - System 1
  - Certificate of constancy of performance of the product Nº 1239/CPR/0801005 dated March 30, 2012

### 6. Declared performance:

Essential characteristics	Performance	Harmonized technical specifications
Reaction to fire	B-s1;d0	EN 438-7:2005
Resistance to fire	NPD	
Water vapour permeability	Wet cup Dry cup	
	110 250	
Resistance to fixings	6mm thickness 8 mm thickness ≥ 10 mm thickness	
	2.000 N 3.000 N 4.000 N	
Direct airborne sound insulation	NPD	
Bonding Strength	NPD <sup>1</sup>	
Flexural tensile strength	PASS	
Thermal conductivity	NPD	
Content of pentachlorophenol	NPD <sup>1</sup>	
Release of formaldehyde	CLASS E1	
Sound absorption	NPD	
Thermal shock resistance	NPD <sup>2</sup>	
Durability: Immersion in boiling water	PASS	
Durability: Density	PASS	

<sup>1</sup> Applicable only to HPL composite panels

<sup>2</sup> Applicable only to panels intended for external use

- The performance of the product identified in point 1 is in conformity with the declared performance in point 6
- This declaration performance is issued under the sole responsibility of the manufacturer identified in point 2
- Signed for and on behalf of the manufacturer by: Iñigo Rodrigo (General Director)

Signature::



**Parklex®**  
www.parklex.com

Place and date of issue:

Bera, the 31<sup>st</sup> of May 2017